

# WHEEL COVER SET

## Technical Data Sheet

### Features:

- Permeable to air and water vapour
- Antistatic
- Abrasion resistant
- Lint-free
- With elastic band
- 68 g/m<sup>2</sup>

### Content :

- Sets of 4 pieces.
- Box content: 50 sets



### Use:

- Dirt protection
- Paint protection

### Technical data

Physical data	Unit	Method	Value
Longitudinal tear resistance	kg / 5 cm	JIS L 1096 SP3035	7,0
Transverse tear resistance	kg / 5 cm	JIS L 1096 SP3035	3,5
Longitudinal tensile strength	g	IST 100.1(95) Elmendorf	1.216
Transverse tensile strength	g	IST 100.1(95) Elmendorf	544
Longitudinal bending resistance	%	ASTM D5034: 1990	65,1
Resistance to transverse bending	%	ASTM D5034: 1990	81
Water Resistance: Hydrostatic Pressure Test	mm H2O	IST 80.4(95)	2.650
Breathable: Airflow in 0.5 inch Water depth: Layer PP Spunbond (cm <sup>3</sup> /cm <sup>2</sup> .S)): Outer layer (cm <sup>3</sup> /cm <sup>2</sup> .S.):		ASTM D737-95: 1980	1,5 below 0,2
Value of water vapor penetration	g/m <sup>2</sup> /24h	JIS L 1099A	3.896,80- 4.412,80
Resistance by PE layer side of the PP layer Spunbond	g	Widht: 100 mm	530
Antistatic properties –Resistance in the surface	Ohm	PrEN 1149-1	4,5 109