

MASKING TAPE



Technical Data Sheet

Backing: Crepe paper.

Adhesive: Rubber-Resing.

Color: white, yellow.

Temperature Resistance (1 hour.): 80°C.

Guarantee: The product and his functionality are guaranteed for a period of SIX MONTHS

Technical properties		Units	Values	Acceptable	Test Method
Thickness	Total	μ	125	±20	PSTC33
	Backing		90		
Weight	Total	g/m3	94	±8	ISO 536
	Backing		59	±6	
	Adhesive		35	±2	
Adhesion to	Steel	N/25mm	4,8	±2,3	PSTC 101
	backing		2,7	±1,2	
Tangential adherence		Min.	15	>5	PSTC 107
Tensile strength		N/25mm	87,5	±18	PSTC 31
Elongation to break		%	8	±3	PSTC 31
Rolling Ball Tack		cm	1	±2	PSTC 6

Conditions of conservation of the product

- Must be stored in dry place and protected from direct solar light.
- Must be stored below 30°C.
- If the product has been exposed to temperatures lower than 18°C before use; it has to be stored between 18°C and 30°C to restore his quality.
- Avoid any type of graze or lateral incision. Do not open the boxes or pallets with cutter or with any other type of cutting object.
- It doesn't have to be exposed to overloads that might cause crushing.