



# TRIM LIFTING-MASKING TAPE

## Technical Data Sheet

### DESCRIPTION

Available only in countries with a valid patent. Plastic strip on a self-adhesive tape improve masking of new windshields and windows in 10 and 15mm width. Makes masking corners easier preventing spraying onto rubbers. Perforated every 38mm for easy application.

Tape features allow supporting temperatures until 70°C. It does not leave residue when removed.

**Sizes: 10mmx10m and 15mmx10m**

### TAPE PROPERTIES

TEST	AVERAGE	MEASURE UNIT	ACCEPTED RANGE	ANALYSIS METHOD
<b>Thickness</b>				
Total	205		195/205	PSTC 33
Support	90		701/110	
<b>Weight</b>				
Total	94	g/m2	86/102	ISO 536
Support	59		53/65	
Adhesive	35		33/37	
<b>Adhesion</b>				
Iron	4,8	N/25mm	2,5/7,25	PSTC 1
Support	2,7		1,5/4	
<b>Adhesion loss</b>	15	Min.	>5	SICAD ICQ 10203

(50° 1 Kg)				
<b>Tension force</b>	87,5	N/25mm	70/112,5	PSTC 31
<b>Elongation breakpoint %</b>	8	%	5/11	PSTC 31
<b>RBT</b>	1	cm	0/3	PSTC 6

Temperature resistance: 80°C 30 min

## STORAGE

Avoid moisture and extreme brightness. Product keeps its properties for 18 months from date of production.

Note: We recommend testing material according to required applications. The company reserves the right to improve or make specific changes and modifications.

## STANDARD PRESENTATION

Rolls with 10 meters in self-dispensing container. Quantity: 30 rolls per box.

Tape is perforated every 38mm.

The technical information is given in good faith, but the user should assure himself that the performance of the product is sufficient for this application.